

## 1 - Triangle → 3D square

### To do

Add perspective projection and model matrices

Change vec2 to vec3

Change assignment to gl\_Position

```
<script id="vertex" type="x-shader">
    mat4 uMVMMatrix = mat4 (1.0, 0.0, 0.0, 0.0,
                            0.0, 1.0, 0.0, 0.0,
                            0.0, 0.0, 1.0, 0.0,
                            0.0, 0.0, -3.333, 1.0 );

    mat4 uPMatrix = mat4 (2.41421, 0.0, 0.0, 0.0,
                          0.0, 2.41421, 0.0, 0.0,
                          0.0, 0.0, -1.002002, -1.0,
                          0.0, 0.0, -0.2002002, 0.0 );

    attribute vec3 aVertexPosition;

    void main() {
        gl_Position = uPMatrix * uMVMMatrix * vec4(aVertexPosition, 1.0);
    }
</script>
```

Make triangle 3d (add z ordinate)

Add second triangle to make a square

Add co-ordinates (initGeometry)

Increase itemsize (initGeometry)

```
function initGeometry() {
    var vertices = new Float32Array([
        //|----- 0 -----| /----- 1 -----| /----- 2 -----|
        //| x   y   z | / | x   y   z | / | x   y   z |
        0.5, 0.5, 0.5, 0.5,-0.5, 0.5, -0.5,-0.5, 0.5, // triangle 1
        0.5, 0.5, 0.5, -0.5, 0.5, 0.5, -0.5,-0.5, 0.5, // triangle 2
        0.5, 0.5,-0.5, 0.5,-0.5,-0.5, -0.5,-0.5,-0.5, // triangle 3
    ]);

    cubeVertexPositionBuffer = gl.createBuffer();
    gl.bindBuffer(gl.ARRAY_BUFFER, cubeVertexPositionBuffer);
    gl.bufferData(gl.ARRAY_BUFFER, vertices, gl.STATIC_DRAW);

    cubeVertexPositionBuffer.itemSize = 3;
```

## 2 - 3D Square → Coloured Cube

### To do

Make cube (add faces)

(connect faces)

(preview with lines)

define vertices, faces

Add colour to faces

```
<script id="vertex" type="x-shader">
    ...
    attribute vec3 aVertexPosition;
    attribute vec4 aVertexColor;

    varying vec4 vColor;

    void main() {
        gl_Position = uPMatrix * uMVMMatrix * vec4(aVertexPosition, 1.0);
        vColor = aVertexColor;
    }
</script>

<script id="fragment" type="x-shader">
```

```

...
gl_FragColor = vColor;
}
</script>

<script type="text/javascript">
var cubeVertexPositionBuffer;
var cubeVertexColorBuffer;
var cubeVertexIndexBuffer;

function initShaderProgram() {
...
gl.enableVertexAttribArray(shaderProgram.vertexPositionAttribute);
shaderProgram.vertexColorAttribute = gl.getAttribLocation(shaderProgram, "aVertexColor");
gl.enableVertexAttribArray(shaderProgram.vertexColorAttribute);
}

function initGeometry() {
var vertices = new Float32Array([
    // Front face
    -0.5, -0.5, 0.5,
    0.5, -0.5, 0.5,
    0.5, 0.5, 0.5,
    -0.5, 0.5, 0.5,
    // Back face
    -0.5, -0.5, -0.5,
    -0.5, 0.5, -0.5,
    0.5, 0.5, -0.5,
    0.5, -0.5, -0.5,
    // Top face
    -0.5, 0.5, -0.5,
    -0.5, 0.5, 0.5,
    0.5, 0.5, 0.5,
    0.5, 0.5, -0.5,
    // Bottom face
    -0.5, -0.5, -0.5,
    0.5, -0.5, -0.5,
    0.5, -0.5, 0.5,
    -0.5, -0.5, 0.5,
    // Right face
    0.5, -0.5, -0.5,
    0.5, 0.5, -0.5,
    0.5, 0.5, 0.5,
    0.5, -0.5, 0.5,
    // Left face
    -0.5, -0.5, -0.5,
    -0.5, -0.5, 0.5,
    -0.5, 0.5, 0.5,
    -0.5, 0.5, -0.5
]);
cubeVertexPositionBuffer = gl.createBuffer();
gl.bindBuffer(gl.ARRAY_BUFFER, cubeVertexPositionBuffer);
gl.bufferData(gl.ARRAY_BUFFER, vertices, gl.STATIC_DRAW);
cubeVertexPositionBuffer.itemSize = 3;
cubeVertexPositionBuffer.numItems = vertices.length / cubeVertexPositionBuffer.itemSize;

cubeVertexColorBuffer = gl.createBuffer();
gl.bindBuffer(gl.ARRAY_BUFFER, cubeVertexColorBuffer);
colors = [
    [0.0, 1.0, 1.0, 1.0], // Front face
    [1.0, 1.0, 0.0, 1.0], // Back face
    [0.0, 1.0, 0.0, 1.0], // Top face
    [1.0, 0.0, 1.0, 1.0], // Bottom face
    [1.0, 0.0, 0.0, 1.0], // Right face
    [0.0, 0.0, 1.0, 1.0] // Left face
];
}

```

```

var unpackedColors = [];
for (var i in colors) {
    var color = colors[i];
    for (var j=0; j < 4; j++) {
        unpackedColors = unpackedColors.concat(color);
    }
}
gl.bufferData(gl.ARRAY_BUFFER, new Float32Array(unpackedColors), gl.STATIC_DRAW);
cubeVertexColorBuffer.itemSize = 4;
cubeVertexColorBuffer.numItems = 24;

var indices = new Uint16Array([
    0, 1, 2,      0, 2, 3,      // Front face
    4, 5, 6,      4, 6, 7,      // Back face
    8, 9, 10,     8, 10, 11,    // Top face
    12, 13, 14,   12, 14, 15,   // Bottom face
    16, 17, 18,   16, 18, 19,   // Right face
    20, 21, 22,   20, 22, 23   // Left face
]);
cubeVertexIndexBuffer = gl.createBuffer();
gl.bindBuffer(gl.ELEMENT_ARRAY_BUFFER, cubeVertexIndexBuffer);
gl.bufferData(gl.ELEMENT_ARRAY_BUFFER, indices, gl.STATIC_DRAW);
cubeVertexIndexBuffer.itemSize = 1;
cubeVertexIndexBuffer.numItems = 36;
}

function draw() {
    gl.bindBuffer(gl.ARRAY_BUFFER, cubeVertexPositionBuffer);
    gl.vertexAttribPointer(shaderProgram.vertexPositionAttribute, cubeVertexPositionBuffer.itemSize,
    gl.FLOAT, false, 0, 0);

    gl.bindBuffer(gl.ARRAY_BUFFER, cubeVertexColorBuffer);
    gl.vertexAttribPointer(shaderProgram.vertexColorAttribute, cubeVertexColorBuffer.itemSize, gl.FLOAT,
    false, 0, 0);

    gl.bindBuffer(gl.ELEMENT_ARRAY_BUFFER, cubeVertexIndexBuffer);

    gl.clearColor(0, 0.5, 0, 1);
    gl.clear(gl.COLOR_BUFFER_BIT | gl.DEPTH_BUFFER_BIT);
    gl.enable(gl.DEPTH_TEST);

    gl.drawElements(gl.TRIANGLES, cubeVertexIndexBuffer.numItems, gl.UNSIGNED_SHORT, 0);
}

```

## 3 – Coloured Cube → Rotated Cube

### To do

Add Rotation

```

<script type="text/javascript">
...
var mvMatrix = mat4.create();
var mvMatrixStack = [];
var pMatrix = mat4.create();

var rotationMatrix = mat4.create();
mat4.identity(rotationMatrix);

function draw() {
    mat4.perspective(45, gl.viewportWidth / gl.viewportHeight, 0.1, 100.0, pMatrix);
    mat4.identity(mvMatrix);
    mat4.translate(mvMatrix, [0.0, 0.0, -4.0]);
    mat4.rotate(mvMatrix, 3, [1, 1, 1]);
    mat4.multiply(mvMatrix, rotationMatrix);

    gl.uniformMatrix4fv(shaderProgram.pMatrixUniform, false, pMatrix);
    gl.uniformMatrix4fv(shaderProgram.mvMatrixUniform, false, mvMatrix);
}

```

## 4 – Rotated Cube → Rotatable Cube

### To do

Input keyboard

mouse

touch

Add flick

Add texture

```
<script type="text/javascript">
  ...
  var mouseDown = false;
  var lastMouseX = null;
  var lastMouseY = null;
  var rvelX = 0;
  var rvelY = 0;

  function degToRad(degrees) {
    return degrees * Math.PI / 180;
  }

  function handleMouseDown(event) {
    mouseDown = true;
    lastMouseX = event.clientX;
    lastMouseY = event.clientY;
  }

  function handleMouseUp(event) {
    mouseDown = false;
  }

  function handleMouseMove(event) {
    if (!mouseDown) {
      return;
    }
    var newX = event.clientX;
    var newY = event.clientY;

    var fudgefactor = 2;
    var deltaX = newX - lastMouseX;
    var deltaY = newY - lastMouseY;
    lastMouseX = newX;
    lastMouseY = newY;

    rvelX = deltaX / fudgefactor;
    rvelY = deltaY / fudgefactor;
  }

  function animate() {
    var newRotationMatrix = mat4.create();

    mat4.identity(newRotationMatrix);
    mat4.rotate(newRotationMatrix, degToRad(rvelX), [0, 1, 0]);
    mat4.rotate(newRotationMatrix, degToRad(rvelY), [1, 0, 0]);
    mat4.multiply(newRotationMatrix, rotationMatrix, rotationMatrix);

    rvelX = rvelX / 1.08;
    if(Math.abs(rvelX) < 0.001) rvelX = 0;
    rvelY = rvelY / 1.1;
    if(Math.abs(rvelY) < 0.001) rvelY = 0;
  }
}
```

## 5 – Rotatable Cube → Dice ???

```
<script id="shader-fs" type="x-shader/x-fragment">
precision mediump float;

varying vec2 vTextureCoord;

uniform sampler2D uSampler;

void main(void) {
    gl_FragColor = texture2D(uSampler, vec2(vTextureCoord.s, vTextureCoord.t));
}
</script>

<script id="shader-vs" type="x-shader/x-vertex">
attribute vec3 aVertexPosition;
attribute vec2 aTextureCoord;

uniform mat4 uMVMatrix;
uniform mat4 uPMatrix;

varying vec2 vTextureCoord;

void main(void) {
    gl_Position = uPMatrix * uMVMatrix * vec4(aVertexPosition, 1.0);
    vTextureCoord = aTextureCoord;
}
</script>

<script type="text/javascript">
var neheTexture;
...
function initShaders() {
    var fragmentShader = getShader(gl, "shader-fs");
    var vertexShader = getShader(gl, "shader-vs");

    shaderProgram = gl.createProgram();
    gl.attachShader(shaderProgram, vertexShader);
    gl.attachShader(shaderProgram, fragmentShader);
    gl.linkProgram(shaderProgram);

    if (!gl.getProgramParameter(shaderProgram, gl.LINK_STATUS)) {
        alert("Could not initialise shaders");
    }

    gl.useProgram(shaderProgram);

    shaderProgram.vertexPositionAttribute = gl.getAttribLocation(shaderProgram, "aVertexPosition");
    gl.enableVertexAttribArray(shaderProgram.vertexPositionAttribute);

    shaderProgram.textureCoordAttribute = gl.getAttribLocation(shaderProgram, "aTextureCoord");
    gl.enableVertexAttribArray(shaderProgram.textureCoordAttribute);

    shaderProgram.pMatrixUniform = gl.getUniformLocation(shaderProgram, "uPMatrix");
    shaderProgram.mvMatrixUniform = gl.getUniformLocation(shaderProgram, "uMVMatrix");
    shaderProgram.samplerUniform = gl.getUniformLocation(shaderProgram, "uSampler");
}

function handleLoadedTexture(texture) {
    gl.bindTexture(gl.TEXTURE_2D, texture);
    gl.pixelStorei(gl.UNPACK_FLIP_Y_WEBGL, true);
    gl.texImage2D(gl.TEXTURE_2D, 0, gl.RGBA, gl.RGBA, gl.UNSIGNED_BYTE, texture.image);
    gl.texParameteri(gl.TEXTURE_2D, gl.TEXTURE_MAG_FILTER, gl.NEAREST);
    gl.texParameteri(gl.TEXTURE_2D, gl.TEXTURE_MIN_FILTER, gl.NEAREST);
    gl.bindTexture(gl.TEXTURE_2D, null);
}

function initTexture() {
    neheTexture = gl.createTexture();
    neheTexture.image = new Image();
    neheTexture.image.onload = function () {

```

```

        handleLoadedTexture(neheTexture)
    }

    neheTexture.image.src = "nehe.gif";
}

function initBuffers() {
    ...
cubeVertexTextureCoordBuffer = gl.createBuffer();
gl.bindBuffer(gl.ARRAY_BUFFER, cubeVertexTextureCoordBuffer);
var textureCoords = [
    // Front face
    0.0, 0.0,
    1.0, 0.0,
    1.0, 1.0,
    0.0, 1.0,
    0.0, 1.0,

    // Back face
    1.0, 0.0,
    1.0, 1.0,
    0.0, 1.0,
    0.0, 0.0,

    // Top face
    0.0, 1.0,
    0.0, 0.0,
    1.0, 0.0,
    1.0, 1.0,

    // Bottom face
    1.0, 1.0,
    0.0, 1.0,
    0.0, 0.0,
    1.0, 0.0,

    // Right face
    1.0, 0.0,
    1.0, 1.0,
    0.0, 1.0,
    0.0, 0.0,

    // Left face
    0.0, 0.0,
    1.0, 0.0,
    1.0, 1.0,
    0.0, 1.0,
],
];
gl.bufferData(gl.ARRAY_BUFFER, new Float32Array(textureCoords), gl.STATIC_DRAW);
cubeVertexTextureCoordBuffer.itemSize = 2;
cubeVertexTextureCoordBuffer.numItems = 24;
...
}

function drawScene() {
    ...
gl.bindBuffer(gl.ARRAY_BUFFER, cubeVertexTextureCoordBuffer);
gl.vertexAttribPointer(shaderProgram.textureCoordAttribute, cubeVertexTextureCoordBuffer.itemSize,
gl.FLOAT, false, 0, 0);

gl.activeTexture(gl.TEXTURE0);
gl.bindTexture(gl.TEXTURE_2D, neheTexture);
gl.uniform1i(shaderProgram.samplerUniform, 0);
...
}

function webGLStart() {
    ...
initTexture();
...
}
</script>
```